

7P SAE J560 Socket with Harness Connector

It is our business to find optimum and safe solutions for various needs in the area of connectors and wires.

For the North American tractor-trailer connector market (SAE J560), we have an all-new solution with outstanding features for our customers.

In comparison with existing product designs, we are able to enhance the application in terms of

- Increased Reliability
- Easier Maintenance
- Lower Cost



Reliability

- Contacts feature individual wire-seals to ensure water-tightness to IPX4
- Cover and mounting flange have active-seals for water tightness to IP54, adaption of corrugated tube
- Premium cover seal and unique central-load spring ensures water tightness (IPX4) when plug is not connected
- Plated contacts and active face seal prevent corrosive damage to contacts when plug is connected
- Flange seal is available to prevent water ingress between the socket and the vehicle or nose box
- Stainless steel mounting bolt bushings allow higher tightening torque



Maintenance

- Modular design for easy repair or replacement
- Harness connector secured to socket housing with secondary locking feature
- 7-pin sockets and harness connector housings are labeled and color coded
 - Green = SAE-J560
 - Yellow = SAE-J560 AUX.
- Custom cover lettering available
- 90° or straight back-shell cover is easily removed and replaced for service and repair



Lower Cost

- No preattached expensive jacketed cable
- No over-mold tooling, process, and materials
- Increased flexibility of harness supplier selection
- Production process for harness maker is commonized with all other vehicle component harnesses
- Contact crimping and insertion can be performed by any harness manufacturer
- Lower weight contributes to lower operating costs